

PG 3212

ISO 9001-2000 certificated



**720x740 dpi Xaar 360 plus heads
for more details
Contact Main Agent**

1 year warranty
(except non-warranty spare parts)

**Sales and service net
covered worldwide**

WWW.AARDVARK-DIGITAL.COM

UK Main Agent
Aardvark Digital, Unit 12, Severnside Trading Estate, Sudmeadow Road,
Hempsted, Gloucester GL2 5HS Telephone +44 (0)1452 520320

Technical Specifications

PG SERIES INK-JET PRINTER

MODEL	PG2512XL-S	PG3212XL	PG3212XL-S
PRINT TECH	Piezo continuous drop-on demand (DOD)		
PRINT HEAD	8 / 12 XJ-128 / 200 Plus	8 / 12 XJ-128/360 PLUS	
PRINT RESOLUTION	Max 360x740dpi	Max 720x740dpi	
PRINTHEAD CLEARANCE	3mm - 5mm off media		
IMAGE SIZE	2.50mtr/8.20ft	3.20mtr/10.49ft	
MEDIA SIZE	2.55mtr/8.36ft	3.25mtr/10.66ft	
PRINTING SPEED	PGXX12/XL-S 2 Pass (360x370dpi) 28sq.m/hr 4 Pass (360x740dpi) 14sq.m/hr	PGXX12/XL 4 Pass (360x740dpi) 22sq.m/hr 8 Pass (720x740dpi) 11sq.m/hr	
INK TYPE	Solvent C.M.Y.K or C.M.Y.K.Lc.Lm		
MEDIA TYPE	PVC Banner, Vinyl, Coating Film, Mesh etc		
MEDIA TRANSMISSION	Roll to Roll		
	PCI high speed, USB (Option), Lan (Option)		
INTERFACE	SAI Photoprint RIP Software		
HEATING SYSTEM	Front and back heater equipped		
AUTO TAKE-UP	Equipped as standard		
VENTILATION	Optional		
PACKING SIZE	3.70 x 0.88 x 1.45 mtr (12.14 x 2.89 x 4.76 ft)	4.40 x 0.88 x 1.45 mtr (14.44 x 2.89 x 4.76 ft)	
GROSS WEIGHT	532 kg / 1172.84 lbs	616 kg / 1358.02 lbs	
POWER REQUIREMENT	110V / 220v > 10A, 50 / 60 Hz		
ENVIROMENT	Temperature: 20 - 25 C	Humidity: 40% - 70% RH	